

LASERMARK®

Gizmo II & III Laser Cross Levels

Easily Level and Plumb With Self-Leveling Red Laser Lines

- Independent Laser Diodes Produce Clear and Precise Reference Lines
- Magnetically Dampened Internal Compensator Stabilizes Quickly
- Automatic Shut-Off When Out Of Self-Leveling Range
- Ideal For Accurate Interior Leveling and Plumbing Applications: Drop Ceilings, Floors, Walls, and More!




CST/berger


MADE IN USA

LASERMARK®


- Use For:** Interior Decorating • Machinery Installation • Finish Carpentry • Drop Ceiling Installation • Stenciling & Wallpaper Application • Grading • Masonry • Aligning 90° Joints & Edges • Septic Work • Plumbing • Marking Elevation • Aligning Wall Fixtures • Cabinets & Shelves • Floor & Wall Tile Installation • Walls & Partitions • Wainscoting • Remodeling • Door, Wall & Window Framing



Leveling cabinetry, applying wallpaper borders (Gizmo II with Laserpole)



Aligning floor and wall tile (Gizmo II or III)



Using 90° reference to erect walls or partitions, install electrical outlets (Gizmo III)

These new and improved Gizmo laser cross levels offer the versatility to do countless leveling, plumbing, and alignment jobs. Don't worry about leveling screws or level vials; the self-leveling Gizmo ensures accurate results. Simply place on a table, the floor, a tripod, or on any stable surface and turn it on.

Standard Features

- One person, push button operation
- Emits eye-safe visible red laser light
- Separate laser diodes produce bright and sharp laser reference lines
- Use horizontal (level) and vertical (plumb) lines together, or separately on Gizmo II; use laser "cross" and/or 90° plumb line on Gizmo III
- Heavy duty magnetically dampened compensator eliminates error by self-leveling the lasers
- Broad $\pm 5^\circ$ self-leveling range
- "Out of leveling range" sensor triggers an automatic shut-off mechanism to ensure accurate results
- Includes custom padded carrying case, wall/tripod mount with $\frac{5}{8}$ " x 11 mounting thread, batteries, and instruction manual
- **90 day warranty against manufacturer's defects**

Specifications

- **Accuracy:**
Leveling: $\frac{1}{8}$ " at 30' (3mm at 9m)
Horizontal/Vertical Line (end to end): $\pm \frac{1}{16}$ " at 10' (± 1.5 mm at 3m)
90° Reference (Vertical), Gizmo III: $\frac{1}{8}$ " at 30' (3mm at 9m)
- **Line Length:** Approx. 45' at 30' (14m at 10m) target distance
- **Recommended Working Range:** Up to 32' (10m), dependent upon illumination of work area
- **Laser Diode:** 635nm. Gizmo II, Two diodes; Gizmo III, Three diodes
- **Fan Angle:** 60°, Horizontal & Vertical
- **Self-Leveling Range:** $\pm 5^\circ$
- **Self-Leveling Speed:** ≤ 3 seconds
- **Weight:** Instrument & Mount, 1.8 lbs. (0.9kg); Carrying Case, 0.7 lbs. (0.3kg)
- **Power:** Three (3) "AA" cell (Alkaline recommended)
- **Battery Life:** Continuous use at 68°F (20°C), variable in colder temperatures: 1 diode on, 25 hours; 2 diodes on, 20 hours; 3 diodes on (Gizmo III), 15 hours

Gizmo Models

- #57-GIZMO-2 LaserMark® Gizmo II Laser Cross, two diodes, with tripod/wall mount
- #57-GIZMO-3 LaserMark® Gizmo II Laser Cross, three diodes with 90° reference window, with tripod/wall mount

LaserMark® Laser Platforms

Our laser poles extend floor to ceiling or within a doorjamb for a highly adaptable laser level platform. The slim profile of these tools fit into tight spaces or corners. $\frac{5}{8}$ " x 11 mounting stud on all models.

LaserMark® Laserpole—Four-section pole is built of a lightweight aluminum core protected by hi-vis plastic tubing. Add or remove 2' sections or use telescoping top section to adjust to desired height. Quick clamping platform adjusts from 4" up to 98" (10cm to 250cm).


#58-LP12 Laserpole, graduated inches, includes carrying bag

LaserMark® LaserJamb™—Hardened aluminum construction. Telescoping top section. Platform adjusts from 4 $\frac{3}{8}$ " up to 148" (12cm to 375cm).

#58-LJ100-C LaserJamb, graduated inches

#58-LJ100-M LaserJamb, graduated metric

#58-LJBAG Padded Carrying Bag for Above



58-LJ100C LaserJamb (shown with Gizmo)



58-LP12 Laserpole (shown with LaserMark® Wizard)

Gizmo Accessories

#57-GLASSES Laser Glasses; improves visibility of red laser beams



Specifications subject to change without notice.

Distributed by: **Latronix AB**
Enhagsvägen 9, 187 40 Täby
Tfn. 08-446 48 30, Fax 08-446 48 39
e-mail: sales@latronix.se
www.latronix.se

LATRONIX
Laser Systems

CST/berger

CST Corporation
450 S. CIPS Street • P.O. Box 359
Watseka, IL 60970 USA
(815) 432-5237
FAX (815) 432-5390
Toll Free U.S.: (800) 435-1859
http://www.cstsurvey.com
sales@cstsurvey.com

Berger Instruments Division
50 Messina Drive
Braintree, MA 02184 USA
(781) 848-7702
FAX (781) 848-8022
Toll Free U.S.: (800) 343-6853
bergersales@cstsurvey.com

Chicago Steel Tape

Berger Instruments

Magna-Trak®

LaserMark®

Tru-Lock™
P/N 00-GIZMO2/3 GG0200